

2. *Qualification.*—A pass in the Lower Secondary Examination or a certificate of having studied in the V Form of a recognised High School.

3. *Departmental Tests.*—In addition to the general educational qualifications mentioned above, candidates for appointments may be required to pass such departmental tests as may be prescribed by Government from time to time.

4. As vacancies occur, appointments will be made from the approved lists according to relative order of mention therein of the names of candidates.

5. *Age Limit.*—The maximum age for entry into service will be 28 years in the case of candidates of Backward Communities and 25 years in the case of others.

6. The candidates must be prepared to take up service in any part of the Mysore State.

7. The candidate appointed will be started as a probationer in the Unit of Recruitment and will on the cessation of the temporary or acting vacancy in which she is appointed, be as far as possible, continued and provided in other vacancies of the same class till she is finally absorbed. She will ordinarily start only at the bottom of the service in the class to which she is appointed and will be on probation for a period of one year. She will also be liable to be transferred to any part of the State.

8. Intending candidates should submit their applications in duplicate in the prescribed form, together with copies of testimonials, etc., so as to reach the undersigned on or before 11th December 1939 (candidates in service should submit their applications through their official superiors).

9. The applications of the candidates whose names are already included in the Central Recruitment Board approved lists and who are already in service, will not be considered.

10. No notice will be taken of applications that are received after the due date or are not submitted in the prescribed form or do not furnish all the particulars required in the various columns of the forms. Applications from the male candidates will not be considered.

By Order,
K. THIPPERUDRIAH,
Secretary,
Central Recruitment Board.

ENGINEERING DEPARTMENT.

BUILDINGS DIVISION, BANGALORE.

Notification dated 22nd November 1939.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Buildings Division, up to 19th December 1939, for constructing four State Officers' quarters, 1st Battalion, Mysore Infantry, Hebbal, Bangalore. An approximate estimate of quantities is given below for one block. These quantities are not guaranteed. The work should be completed by the end of August 1940.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Buildings Division, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

4. Each tender must be accompanied by a deposit of Rs. 1,200 only in cash or Government Promissory Notes, as earnest money, and be superscribed "Tender for constructing four State Officers' quarters, Mysore Infantry, Hebbal, Bangalore," in default of which tenders will be rejected.

5. The final acceptance of any tender will rest with the Superintending Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond, in default of which his tender will be considered cancelled, and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Abstract estimate for constructing State Officer's Quarters, Mysore Infantry, Bangalore.

No.	Items of work	Unit	Rate	Quantity	Cost
			Rs. a. p.		Rs.
1	Earthwork excavation for foundation removing the excavated earth to a distance of not exceeding 50 yards, and filling in basement with excavated earth including watering, tamping and consolidating in layers of 6" thick	C.yds.	0 3 0	118	
2	Burnt stone jelly concrete in lime mortar (1:2½:4) for foundation laid and well consolidated in layers of 6"	C.ft.	0 3 0	1,071	
3	Burnt size stone in mud, in courses of not less than 6" high, with bond stones laid 6' apart for foundation	"	0 3 0	1,700	
4	Burnt size stone in mud, in courses not less than 6" high with bond stones 6' apart including all quoins neatly dressed to 2" wide at the corners (to a depth of 2' exposed portion), etc., complete for basement	"	0 3 3	671	
5	Burnt stone slabs 6" thick, 2 line dressed for the exposed faces and one line dressing on all other surfaces, set in mortar, for the outer walls of basement and steps	S.ft.	0 5 6	385	
6	Burnt stone slab, 6" thick, one line dressed on all surfaces, for the inner walls of basement, lintel slabs of doors, sills and lintels of windows and ventilators	S.ft.	0 4 6	527	
7	Burnt brick in lime mortar for superstructure	C.ft.	0 3 9	2,483	
8	Burnt brick in clay for superstructure	"	0 3 0	888	
9	Wire cut quadrant bricks, in lime mortar for pillars, with R.C.C. bond slabs in two places in every pillar	"	0 10 0	23	
10	Burnt stone slabs pillars 6" thick one line dressed with bed slabs, etc., complete	S.ft.	0 5 6	79	
11	Partition wall with burnt brick in cement mortar, brick on edge 3" thick with Xmet reinforcement in every 3rd course including lime mortar plastering, etc., complete	"	0 6 0	145	
12	Teakwood partition with verticals uprights 1" thick plank, 7' high including 2 coats of varnish, etc., complete	"	0 8 0	98	
13	Plastering with chunam mortar ¾" thick, and rounding off the corners and side edges of doors and windows, with cement mortar and smooth rendering, etc., complete	Sqr.	3 0 0	71.56	
14	Pointing the stone masonry basement with cement mortar, by raking out the joints ¾" deep and lining nicely and watering for some days, etc., complete.	"	2 8 0	3.77	
15	Colour washing 2 coats	"	0 5 0	19.81	
16	White washing 2 coats	"	0 4 0	51.75	
17	Rolled steel girders of British standard specifications, Tata's tested and Dorman Long make, including lifting, hoisting and boxing with cement mortar and terrace bricks reinforced with galvanized steel tex tied from above, with two coats of anti-corrosive paint, etc., complete	Cwts.	16 0 0	30.91	
18	R.C.C. chejja over the windows 3" thick at the wall and 2" thick at the end of chejja with necessary reinforcements (cement concrete to consist of 1 cement 2 sand and 4 of chips, i.e., batony jelly) including plastering, colour washing, etc., complete	S.ft.	0 8 0	133	
19	Roofing with reinforced cement concrete (1:2:4) 5" thick terrace with necessary reinforcements to take a super load of 1½ cwts. per sq.ft. for spans up to 10' (as per design which will be furnished during construction) with R.C.C. chejja projected 2½' wide from the roof around the building having 3" thick at the end of chejja, including chunam plastering for the ceiling and both faces of chejja, the top of roof to have surki concrete to a depth not less than 3" thick, over the cement concrete slab, over which 2 courses of flat tiles laid on to a proper slope to drain off rain water and nicely plastered over.	Sqr.	65 0 0	33.75	

No.	Items of work	Unit	Rate	Quantity	Cost
			Rs. a. p.		Rs.
20	Flooring with cement concrete (1:2:4) $1\frac{1}{2}$ " thick over a bed of 4" thick lime concrete with topping of $\frac{1}{2}$ " thick red ochre and lines cut nicely to design of tiles	Sqr.	18 0 0	17.08	
21	Flooring with burnt stone slabs 3" thick over a bed of 3" thick surki concrete and pointing the surface with cement and lined nicely	"	20 0 0	0.60	
22	Wrought iron railing as per design to be furnished during construction, 3' high between pillars of front verandah	R.ft.	2 8 0	20	
23	Teak wood doors of well seasoned Mysore teak, 3" x 5" frames, $1\frac{1}{2}$ " thick shutters $\frac{1}{2}$ " panelled at bottom and $\frac{3}{4}$ " glazed at top without bottom sills with $\frac{1}{8}$ " thick glass of variety to be specified with required type of ventilators complete with Acme brass or copper oxidized fittings such as rim locks with handles, hinges, hooks, barrel tower bolts of suitable size, etc., including varring the sides for the seat in brick work with 2 coats of approved Dulux or Johnson & Nickelson or any kind of water proof varnish, etc., complete as per specification	S.ft.	1 6 0	294	
24	Teak wood windows of well seasoned Mysore teak, with frames 3" x 4" having fully glazed shutters 1" thick, with low red shutters for the ventilators fixed to them including usual iron fittings (to be furnished during construction) $\frac{3}{4}$ " dia. iron bars placed $4\frac{1}{2}$ " to 5" C to C with 2 coats of varnish for inner windows and 2 coats of paint for outer ones (to be furnished during construction) etc., complete	"	1 8 0	180	
25	Teak wood ventilators 3" x 4" with glazed shutter 1" thick with usual fittings and 2 coats of required painting (design will be furnished during construction)	"	1 2 0	45	
26	R.C.C. perforated ventilators $1\frac{1}{2}$ " to 2" thick by 2" frame around with necessary reinforcements (design to be furnished during execution)	"	0 12 0	9	
27	Rain water down pipes of cast iron 3" square with bends, etc., complete	R.ft.	1 4 0	26	
28	Smoke chimney in kitchen as per design to be furnished during execution	Each	20 0 0	1	

M. K. RAJAM IYENGAR,
Executive Engineer.

MISCELLANEOUS DEPARTMENTS.

OFFICE OF THE EX-OFFICIO CONTROLLER OF PATENTS AND DESIGNS IN MYSORE, BANGALORE.

No. C2. Pat. 199—38-39, dated 16th November 1939.

NOTICE OF ACCEPTANCE OF APPLICATION FOR PATENT

No. 199 of 1938-39, dated 18th April 1939.

Notice is hereby given that all persons interested in opposing the grant of a patent on the application referred to below may at any time within three months of the date of this notification give notice to the *Ex-officio* Controller of Patents and Designs in Mysore, in the prescribed Form No. 5 of such opposition.

Les Usines De Melle of France.

"Improvements in or relating to the extraction of Glycerine from Glycerine containing Liquids."

Any one desiring to inspect copy of the specification of the above may call at the Office of the *Ex-officio* Controller of Patents and Designs on any working day between 11 A.M. and 5 P.M. A sum of rupee one will be charged for such inspection.

L. MUNISWAMY,
For *Ex-officio* Controller of Patents and Designs.